



NOTE
 THE SANITARY FLANGE IN THE
 DRAWING CONFIRMS TO ISO-2852.

PROPRIETARY
 REPRODUCTION OR DISTRIBUTION
 WITHOUT WRITTEN CONSENT OF
 NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	REQUIREMENTS—UNLESS OTHERWISE SPECIFIED				CONTRACT NUMBER	—	NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 358-220, RICHMOND HILL, ON L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com								
	GENERAL				CLIENT	—	TITLE								
MATERIAL	SS-316L	1. DIMS ARE IN MM 2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.3 (1982) 3. MACHINE FINISH 125 MICRO INCH RMS 4. INTERNAL RADII .015 5. BREAK SHARP CORNERS .005 TO .015				CONTRACTOR	—	DRAWN	CHRIS RAG.S	DATE	03/10/2017	2" SS-316L RING VAC ASSEMBLY DRAWING			
FINISH	—	LIMITS				DESIGN	—	CHECKED	ASHISH	PROJECT	—	SCALE	1:1		
		1. LINEAR DIMS: 1/16" = .005 1/32" = .010 1/64" = .020				MANUFACTURING	—	MATERIALS	—	SIZE	C	CAGE CODE	—		
		2. ANGLES = ± 1/2°				STRESS	—	ELECTRICAL	—	DWG NO	—	OUTLINE DRAWING	RELEASE	P 1	
		3. RUNOUT .010 THRU				MATERIALS	—	MATERIALS	—	REV	—	—	—	1	
		4. HOLES IN ACCORDANCE WITH AND 10387				MECHANISM	—	ELECTRICAL	—	SCALE	1:1	CAD NO	—	SHEET	1 OF 1
		NEXT ASSEMBLY	USED ON	QTY PER	PART NO										
		PART NO	—	—	—										