



Ø0.26" [Ø6.50] X 3 HOLES THRU

0.73" [18.50] 0.73" [18.50]

0.39" [10.00]

1.18" [30.00]

1.97" [50.00]

Ø0.28" [Ø7.00] X 2 HOLES THRU ON 1.78" [45.09] PCD

Ø 1.26" [32.00]

R0.08" [R2.00]

120.00°

1.40" [35.50]

2.17" [55.00]

2.24" [57.00]

0.08" [2.00]

90.00°

**PROPRIETARY**  
REPRODUCTION OR DISTRIBUTION  
WITHOUT WRITTEN CONSENT OF  
NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	
MATERIAL	SS-304
FINISH	BUFFING

REQUIREMENTS—UNLESS OTHERWISE SPECIFIED	
GENERAL	
1. DIMS ARE IN INCHES (MM)	
2. DIMENSIONS AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5 (1994)	
3. MACHINING FINISH 125 MICRO INCH RMS	
4. INTERNAL RADI .015	
5. BREAK SHARP CORNERS .005 TO .015	
TOLERANCES	
1. LINEAR DIMS	
FRACTIONS = .005	
DECIMALS = .010	
ANGLES = ± 1/2°	
2. ANGLES	
= ± 1/2°	
3. RADIUS .010 THRU	
4. HOLES IN ACCORDANCE WITH AND 10:87	

CONTRACT NUMBER	---
CLIENT	---
CONTRACTOR	---
DATE	30/01/2019
DESIGN	---
LES	---
PROJECT	---
FINISH	---
MANUFACTURING	---
MATERIALS	---
ELECTRICAL	---

NEX FLOW AIR PRODUCTS CORP.			
10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3G7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com			
TITLE			
MOUNTING BRACKET FOR 1" RING VAC			
SIZE	CAGE CODE	DWG NO	RELEASE
---	---	39001S	P 1
SCALE	CAD NO	SHEET	OF
1:1	---	1	1

PART NO SEE TABLE