



Ø0.26" [Ø6.50] X 3 HOLES THRU

Ø0.28" [Ø7.00] X 2 HOLES THRU ON 1.98" [50.34] PCD

PROPRIETARY
REPRODUCTION OR DISTRIBUTION WITHOUT WRITTEN CONSENT OF NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	
MATERIAL	SS-304
FINISH	BUFFING

REQUIREMENTS—UNLESS OTHERWISE SPECIFIED	GENERAL
1. DIMS ARE IN INCHES [MM]	
2. DIMENSIONS AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)	
3. MACHINE FINISH 125 MICRO INCH RMS	
4. INTERNAL RADI .015	
5. BREAK SHARP CORNERS .005 TO .015	
LIMITS	
1. LINEAR DIMS.	
+.002 = .005	
-.002 = .010	
+.001 = .005	
-.001 = .005	
2. ANGLES	= ± 1/2°
3. RUNOUT	.010 TIR
4. HOLES IN ACCORDANCE WITH AND 10387	

CONTRACT NUMBER	—
CLIENT	—
CONTRACTOR	—
DRAWN	CHRAG
DATE	30/01/2019
CHECKED	—
DESIGN	LES
PROJECT	—
Q.A.	—
STRESS	—
MANUFACTURING	—
THERMAL	—
MATERIALS	—
ELECTRICAL	—
MECHANISM	—

NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com					
TITLE MOUNTING BRACKET FOR 1-1/4" RING VAC					
SIZE	CAGE CODE	DWG NO	RELEASE	REV	
—	—	39002S	P	1	
SCALE	1:1	CAD NO	SHEET	1	OF 1

PART NO SEE TABLE