



THIRD ANGLE PROJECTION		REQUIREMENTS - UNLESS OTHERWISE SPECIFIED	
MATERIAL		GENERAL	
AL		1. DIMS ARE IN INCHES (MM)	
		2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5-2009	
		3. MACHINE FINISH 3.175 MICRONS RMS	
		4. INTERNAL RADIUS 1 TO 4	
		5. BREAK SHARP CORNERS 1 TO 4	
FINISH		LIMITS	
		1. LINEAR DIMS: $\pm .005$ $\pm .002$ $\pm .001$	
		2. ANGLES = $\pm 1/2^\circ$	
		3. HOLE OUT .010 THR	
		4. HOLES IN ACCORDANCE WITH AND 10397	
PART NO	INCR ASSEMBLY	USED ON	QTY PER PART NO
			ASST
		CONTRACT NUMBER -	
		CLIENT	
		CONTRACTOR	
		DATE	
		DESIGNED	
		CHECKED	
		PROJECT	
		MATERIALS	
		MANUFACTURING	
		STRESS	
		MECHANICAL	
		ELECTRICAL	
TITLE		SCALE	
X-STREAM SUPREME PNEUMATIC CONVEYOR		1:1	
NEX FLOW AIR PRODUCTS CORP 1050 YONGE STREET, UNIT 250-220, RICHMOND HILL, ON L4C 3Y7 TEL: (416) 410-1313 & FAX: (416) 410-1000 www.nex-flow.com		SPEC. NO. XSPCE0-01	
SHEET 1 OF 1		REV	
		P	
		-	